

MDI AseptiSure WS are low protein binding hydrophilic PVDF membrane mini cartridge filters offering serial filtration incorporating a large pore size upstream membrane to protect the downstream membrane for enhanced throughput.

These cartridge filters are validated to meet compendia and regulatory requirements and are well characterized. They meet key process requirements such as absolute retention efficiency, extremely low extractables, high throughputs, wide chemical compatibility and other important characteristics.

Key features

- Absolute retention
- 100% integrity tested
- Low protein binding
- Low extractables

Applications

- Cell culture media
- Growth regulators
- Small Volume Parenterals



Complies with USFDA 21 CFR 210.3(b)(6)

Meets and Exceeds USFDA 21 CFR 177.1520

Specifications

Pore Size
0.1 µm

Materials of Construction

Membrane	Hydrophilic PVDF
Support Layer	Polyester
Plastic Components	Polypropylene

Microbial Retention

LRV >7 for *A. laidlawii* (ATCC 23206) per cm²

Sterilization

Autoclavable/ Inline steam sterilizable at 135°C for 3 cycles of 30 minutes each

Maximum Operating Temperature

80 °C @ ≤ 30 psi (2 Kg/cm²)

Maximum Differential Pressure

50 psi (3.5 Kg/cm²) @ 25 °C

Bubble Point

≥ 31 psi (2.18Kg/cm²) with 50% IPA/Water Solution

Toxicity

Passes Bioreactivity test, In Vivo, as per USP <88> for Class VI plastics

Cytotoxicity

Passes Biological Reactivity Tests, In Vitro, USP <87> for cytotoxicity

Bacterial Endotoxin

Aqueous extracts exhibit < 0.25 EU/ml as established by Limulus Amebocyte Lysate (LAL) Test as per USP <85>

Fiber Release

Passes test as per USP and comply with USFDA 21 CFR Part 210.3(b)(6) for fiber release

Particle Release:

The filtrate complies with USP <788> test for particulate matter in injections

TOC and Conductivity

Meets the WFI requirements of USP for TOC <643> and Conductivity <645> after flushing with a specified volume of WFI

Extractables with WFI

Passes test as per USP <661>

Oxidizable Substances

Passes test as per USP <1231>

Ordering Information

Type		Size		Pore Size		Adaptor		Elastomer		Sterility		Pack Size	
	Code	Length and EFA	Code		Code		Code		Code		Code		Code
AseptiSure WS (0.2 µm upstream)	CWH1	2.5" (1000 cm ²)	50	0.1 µm	36	4463	E0	Silicone	SS	Non-Sterile	1	1	01
		5" (2000 cm ²)	53			4463B	H0						
AseptiSure WS (0.45 µm upstream)	CWHX					4440	U0	*G0 adaptor code is not available with any elastomer. Please mention XX in place of elastomer code while ordering **Adaptor code F0 is available only in 5" cartridge filters					
						Seal-K	G0*						
						Seal-O	F0**						
						Seal-M	J0						

EFA: Effective Filtration Area

Example

CWHX	53	36	E0	SS	1	01
------	----	----	----	----	---	----